

RENTAL AND SALE

OEG Offshore provide a 10ft offshore cryogenic tank for the safe handling, transportation and storage of liquid nitrogen, primarily for wells, pipeline, and processing equipment operations. Our tanks have a hold time of 25 days and have also been designed with Dual try-cock valves for ease of use and lower roof plates meaning that the tanks can be stacked with their slings/shackles in position.

These T75 cryogenic tanks are designed and manufactured to meet DNV 2.7-1, EN 12079, IMDG/ADR/RID, ISO, CSC and NORSOK M501 standards.



FEATURES

- ▶ Designed, manufactured and fully certified to DNV 2.7-1 / EN 12079 standards
- ▶ T75 UN portable tank approved under IMDG / ADR / RID O Other design approvals – CSC, USDOT, ASME VIII, AS 1210
- ▶ Inner shell – stainless steel
- ▶ Outer jacket – carbon steel
- ▶ 88 psi working pressure
- ▶ 7,900 litre capacity
- ▶ 25 day holding time
- ▶ Dual try-cock valves
- ▶ Lower roof plates to allow stacking with slings / shackles remaining in situ

OPTIONS

- ▶ GPS tracking
- ▶ Customer Paint Colour
- ▶ Shelves
- ▶ Hooks
- ▶ Bars
- ▶ Brick Net
- ▶ Ratchet Straps
- ▶ Door Gear & Seals

CONTAINER TYPE	EXTERNAL DIMENSIONS (MM)	TARE WEIGHT (KGS)	PAYLOAD (KGS)	MAX GROSS WEIGHT (KGS)
10ft Cryogenic Tank	2991 x 2438 x 2591	5370	6065	11435

E & OE

All dimensions and weights are accurate at the time of creation. Please check exact specifications of units when ordering.