

25 BBL IM 101 TRANSPORT TANKS

RENTAL AND SALE

OEG's fleet of IM 101 tank containers provide the ideal solution for the transportation of hazardous materials such as toxics, corrosives, and flammable liquids with flash points below 32 degrees fahrenheit. The 25bbl IM101 tanks are designed, constructed and test to DNV 2.7-1 and API RP 2A that meets all applicable requirements of the ASME Boiler and Pressure Vessel Code, Section VIII, Division 1 or US Federal Register 49CFR section 270 & 271, configuration in both T2 or T4.

Equipment supplied meets the specific requirements of the latest international standards and approvals under IMDG, ADR/RID, DNV 2.7-1 & EN 12079 or ISO 10855.



FEATURES

- ▶ SEPco OPS0055 certified
- ▶ Stackable
- ▶ EPOXY lined for easier cleaning
- ▶ Ladder on valve end with full length OSHA walkway
- ▶ 3" BFV, male camlock w/cap, internal valve and remote closure equipped with fusible link.
- ▶ Tank constructed with 3/8", SA-36 plated cylinder, and 3/8" SA-516, GR 70 PL heads.
Pressure and vacuum relief vent flow rate of 4208 cu. ft. of free air per minute as required by CFR 49, 178.270-11. Set at 63.8 PSI/6 in vacuum.
- ▶ Rental and Sale

OPTIONS

- ▶ Bespoke design and modifications as purchase option

CONTAINER TYPE	EXTERNAL DIMENSIONS (MM)	TARE WEIGHT (KGS)	PAYLOAD (KGS)	MAX GROSS WEIGHT (KGS)
25 bbl IM-101/DNV Liquid Transport Tank	2590 x 1727 x 2235	2495	11115	13610

E & OE

All dimensions and weights are accurate at the time of creation. Please check exact specifications of units when ordering.

Version: 2021-03-03

First Choice in Cargo-Carrying Units, Transportable Tanks, A60 Cabins and associated services worldwide for Sale and Rental



sales@oegoffshore.com
www.oegoffshore.com