

20ft (6m) Dual Zone Refrigeration / Freezer Module



DNV 2.7-1 REFRIGERATED MODULES FOR RENTAL AND SALE

OEG Offshore's extensive fleet of refrigeration and freezer solutions provide temperature controlled conditions for the transportation and storage of foodstuffs to offshore locations. Available in a range of sizes the refrigerated units can be hooked up to the vessel or platform's own power supply.

All modules are certified in accordance with DNV 2.7-1 and EN 12079 standards and are available from our global base network. A range of optional extras and customisations can also be specified.

Equipment supplied meets the specific requirements of the latest international standards & approvals
DNV 2.7-1 / EN 12079 or
ISO 10855, SEPco, API, DOT,
CFR, ASME VIII DIV 1., IMDG,
ADR/RID & UK CAA CAP 43.



20ft (6m) Dual Zone Refrigeration / Freezer Module



The dual zone refrigerated container can provide consistent chilled or frozen temperatures for food transportation and storage.

KEY FEATURES

- > Temperature settings ranging from -24°C to +24°C
- > Electronic control panel enables the adjustment of internal temperature and control of cooling plant function
- > Hygienic, easy-to-clean GRP interior
- > Double wing door with heavy duty hinges
- > Man trapped alarms in both compartments for personnel safety
- > Container and sling assemblies are rated to DNV 2.7-1 and CSC approved
- > 3 phase 50Hz 380-415V, 60HZ 440-460V
- > Internal cold doors
- > Rear protection gates
- > Removable airflow, high grip flooring
- > Internal lighting
- > Power hook up cable
- > Flashing strobe beacon when unit is powered

OPTIONS

- > Butchers door curtain
- > Removable shelving system
- > Diesel generator
- > Custom paint colour & customer logos
- > GPS tracking

TECHNICAL SPECIFICATION

20FT (6M) DUAL ZONE REFRIGERATED / FREEZER MODULE	METRIC (MM)	IMPERIAL (FT/INCHES)
EXTERNAL DIMENSIONS	6050 x 2440 x 2890	19'11" x 8'1" x 9'6"
INTERNAL DIMENSIONS: Twin zone, 2 zones each measuring:	2530 x 1990 x 2200	8'3" x 6'7" x 7'3"
INTERNAL DIMENSIONS: Single zone, 1 zone measuring:	5020 x 1990 x 2200	16'6" x 6'7" x 7'3"
TARE WEIGHT	7500 Kg	16535 lbs
MAX. GROSS WEIGHT	15000 Kg	33069 lbs
PAYLOAD	7500 Kg	16535 lbs

E & OE
All dimensions and weights are accurate at the time of creation. Please check exact specifications of units when ordering.

First Choice in Offshore Cargo Carrying Units, Compactors and Modules for Sale and Rental worldwide



sales@oegoffshore.com
www.oegoffshore.com