

RENTAL AND SALE

OEG Offshore's Intermediate Bulk Containers (IBCs) are rated UN31A for the transportation and storage of hazardous and non-hazardous liquid chemicals.

They are suitable for a variety of applications including the transportation and storage of combustible and flammable raw materials, solvents and solvent based chemical preparations, water treatment chemicals, oil and water based lubricants, down hole chemicals, paints and allied products, resins, pigments and dyes, cleaning and sanitation chemicals, pharmaceutical and food preparations and industrial organics.

OEG can supply a wide range of DNV certified transport frames, racks and containers to safely transport Intermediate Bulk Containers in an offshore environment.

Equipment supplied meets the specific requirements of the latest international standards & approvals.

DOT CFR 49, UN 31A/Y, and IMDG 6.5





KEY FEATURES

- > DOT CFR 49, UN 31A/Y, and IMDG 6.5 compliant
- > 10 gauge, 304 stainless steel with 2B finish
- > One piece body and single seam welding
- > Sloped bottom for virtual 100% discharge
- > 22-5/16" (566 mm) top manway with EPDM gasket and bolted clamp ring
- > 3" fusible cap with lanyard
- > 2" (50.8 mm) top bung fitting with EPDM gasket
- > Stainless steel UN tag
- > Heavy duty lifting lugs/stackable leg positioners
- > 2" (50.8 mm) discharge assembly with 316 stainless steel one piece elbow, locking handle ball valve and plastic plug
- > Full-length valve guard on side drain tanks
- > 6-1/2" (166 mm) leg height and 9-1/4" (235 mm) leg height for center drain tanks
- > Three-way fork lift entry on side drain tanks
- > 350 and 550 gallon models feature a one-piece body and single-seam welding
- > Stackable

TECHNICAL SPECIFICATIONS

NOMINAL CAPACITY	NOMINAL DIMENSIONS (L X W X H)	APPOX. TARE WEIGHT	APPROX. MAX. GROSS WEIGHT	DRAIN CONFIGURATION
454 L (120 US GAL)	1,067mm x 1,219mm x 622mm 42" x 48" x 24.5"	295 lbs (134 kg)	2,205 lbs (1000 kg)	Side Drain
681 L (180 US GAL)	1,067mm x 1,219 mm x 800mm 42" x 48" x 31.5"	347 lbs (157 kg)	3,196 lbs (1450 kg)	Side Drain
1135 L (300 US GAL)	1,067mm x 1,219 mm x 1,143mm 42" x 48" x 45"	430 lbs (195 kg)	5,203 lbs (2360 kg)	Side Drain
1325 L (350 US GAL)	1,067mm x 1,219 mm x 1,295mm 42" x 48" x 51"	475 lbs (215 kg)	6,030 lbs (2735 kg)	Side Drain
1514 L (400 US GAL)	1,067mm x 1,219 mm x 1,448mm 42" x 48" x 57"	534 lbs (242 kg)	6,867 lbs (3115 kg)	Side Drain
1703 L (450 US GAL)	1,067mm x 1,219 mm x 1,600mm 42" x 48" x 63"	594 lbs (269 kg)	7,694 lbs (3490 kg)	Side Drain
2082 L (550 US GAL)	1,067mm x 1,219 mm x 1,905mm 42" x 48" x 75"	630 lbs (286 kg)	9,370 lbs (4250 kg)	Side Drain
3000 L (793 US GAL)	1372 mm x 1372 mm x 1,905mm 54" x 54" x 75"	795 lbs (361 kg)	13,456 lbs (6104 kg)	Side Drain
1325 L (350 US GAL)	1,067mm x 1,219 mm x 1,365mm 42" x 48" x 53.75"	575 lbs (261 kg)	6,030 lbs (2735 kg)	Centre Drain
2082 L (550 US GAL)	1,067mm x 1,219 mm x 1,975mm 42" x 48" x 77.75"	734 lbs (333 kg)	9,370 lbs (4250 kg)	Centre Drain
3000 L (793 US GAL) 2-way fork channel	1372 mm x 1372 mm x 1,975mm 54" x 54" x 77.75"	866 lbs (393 kg)	13,456 lbs (6104 kg)	Centre Drain
3000 L (793 US GAL) 4-way fork channel	1372 mm x 1372 mm x 1,975mm 54" x 54" x 77.75"	1,047 lbs (475 kg)	13,456 lbs (6104 kg)	Centre Drain

E & OE
All dimensions and weights are accurate at the time of creation. Please check exact specifications of units when ordering.



First choice in offshore cargo carrying units, A60 modules
and welfare solutions for sale and rental worldwide

sales@oegoffshore.com
www.oegoffshore.com