

Enviro-Pak[®] C-Series Compactors



FEATURES

- Functions as both a compactor and a baler
- Moving parts completely enclosed to prevent injury
- Hydraulic operated roll back top for easy loading and unloading
- Compacts all types of non-hazardous waste into bag
- In bag compaction at a 5:1 safety ratio
- Slow release door for easy bag removal
- Two hand operation for operator safety
- Filter/can/glass crusher and food grind attachment available
- Reduce disposal costs by reducing waste volume
- ABS approved
- UL listed components
- Meets and exceeds International MARPOL 73/78 Annex V
- Patented



TECHNICAL SPECIFICATION - SINGLE CHAMBER

UNIT	Model 3000C	Model 4000C	Model 5000C
CAPACITY	30 ft ³ / 0.9 m ³	40 ft ³ / 1.1 m ³	50 ft ³ / 1.42 m ³
HEIGHT	107" / 2718 mm	62" / 1575 mm	114" / 2896 mm
WIDTH	56" / 1422 mm	62" / 1575 mm	62" / 1575 mm
DEPTH	83" / 2108 mm	89" / 2261 mm	95" / 2413 mm
DECK SPACE	32 ft ² / 3.0 m ²	38 ft ² / 3.5 m ²	38 ft ² / 3.5 m ²
WEIGHT	3,900 lbs / 1772 kg	4,115 lbs / 1867 kg	4,360 lbs / 1982 kg
COMPACTION FORCE	60,000 lbs / 27216 kg	60,000 lbs / 27216 kg	60,000 lbs / 27216 kg
BAG MODEL	HV96026	HV96030	HV96027
BAG SWL	1,500 lbs / 680 kg	2,200 lbs / 997 kg	2,200 lbs / 997 kg
ELECTRICAL RATING	5HP 230/460V 7.8/15.5 AMP	5HP 230/460V 7.8/15.5 AMP	5HP 230/460V 7.8/15.5 AMP
AIR REQUIREMENT	100PSI / 75CFM	100PSI / 75CFM	100PSI / 75CFM
CYCLE TIME	96 seconds	96 seconds	96 seconds
OIL CAPACITY	10 GAL / 38 L	10 GAL / 38 L	10 GAL / 38 L

Note: All measurements are rounded up to the nearest whole unit or decimal.

First Choice in Compactors, Balers, Food Grinders, Crushers
and Associated Services

TECHNICAL SPECIFICATION - DUAL CHAMBER

UNIT	Model 3000CC	Model 4000CB	Model 5000CC
CAPACITY	60 ft³ / 1.70 m³	70 ft³ / 2.0 m³	80 ft³ / 2.3 m³
HEIGHT	107" / 2718 mm	108" / 2743 mm	108" / 2743 mm
WIDTH	56" / 1422 mm	62" / 1575 mm	62" / 1575 mm
DEPTH	83" / 2108 mm	89" / 2261 mm	91" / 2311 mm
DECK SPACE	32 ft² / 3.0 m²	38 ft² / 3.5 m²	39 ft² / 3.6 m²
WEIGHT	4,450 lbs / 2018 kg	4,850 lbs / 2200 kg	4,850 lbs / 2200 kg
COMPACTION FORCE	60,000 lbs / 27,216 kg	60,000 lbs / 27,216 kg	60,000 lbs / 27,216 kg
BAG MODEL	HV96026	HV96030	HV96027
BAG SWL	1,500 lbs / 680 kg	2,200 lbs / 997 kg	2,200 lbs / 997 kg
ELECTRICAL RATING	5HP 230/460V 7.8/15.5 AMP	5HP 230/460V 7.8/15.5 AMP	5HP 230/460V 7.8/15.5 AMP
AIR REQUIREMENT	100PSI / 75CFM	100PSI / 75CFM	100PSI / 75CFM
CYCLE TIME	96 seconds	96 seconds	96 seconds
OIL CAPACITY	10 GAL / 38 L	10 GAL / 38 L	10 GAL / 38 L

Note: All measurements are rounded up to the nearest whole unit or decimal.



First Choice in Compactors, Balers, Food Grinders, Crushers
and Associated Services



sales@oegoffshore.com
www.oegoffshore.com