

FEATURES

- Recyclable materials such as aluminum, paper, cardboard, tin, and PETE plastics are separated at the source and compacted
- Compacts recyclable solid waste materials into disposable bags utilizing multiple compaction chambers on a rotating table
- Small footprint enclosed with drip pan and drain plugs
- In bag (woven polypropylene) compaction with a 5:1 safety ratio
- Two hand operation for operator safety
- Optional food grinder attachment or filter crusher available
- UL listed components
- Meets and exceeds International MARPOL 73/78 Annex V
- ABS approved
- Patented



TECHNICAL SPECIFICATION

UNIT	Model R44	Model R6	Model R6x2
CAPACITY	4 Chamber Carousel 4 x 4.5 ft ³ / 0.13 m ³	6 Chamber Carousel 6 x 5.5 ft ³ / 0.16 m ³	8 Chamber Carousel (6) 5.5 ft ³ / 0.16 m ³ (2) 14 ft ³ / 0.4 m ³
HEIGHT	90" / 2286 mm	95" / 2413 mm	126" / 3201 mm
WIDTH	49" / 1245 mm	72" / 1829 mm	86" / 2184 mm
DEPTH	44" / 1118 mm	64" / 1626 mm	79" / 2006 mm
DECK SPACE	15 ft ² / 1.4 m ²	32 ft ² / 3.0 m ²	49 ft ² / 4.6 m ²
WEIGHT	1,860 lbs / 843 kg	3,500 lbs / 1588 kg	5,900 lbs / 2677 kg
COMPACTION FORCE	16,000 lbs / 7620 kg	29,000 lbs / 13154 kg	38,000 lbs / 13154 kg
BAG MODEL	HV96034	HV96035	HV96022 (2) HV96035 (6)
BAG SWL	350 lbs / 159 kg	600 lbs / 272 kg	550 lbs / 250 kg
ELECTRICAL RATING	5HP 230/460V 7.8/15.5 AMP	5HP 230/460V 7.8/15.5 AMP	5HP 230/460V 7.8/15.5 AMP
AIR REQUIREMENT	100PSI / 75 CFM	100PSI / 75 CFM	100PSI / 75 CFM
CYCLE TIME	30 seconds	30 seconds	30 / 66 seconds
OIL CAPACITY	4 GAL / 15 L	7 GAL / 26.5 L	11 GAL / 42.3 L

Note: All measurements are rounded up to the nearest whole unit or decimal.