

Enviro-Pak® Tuff Gut Food Grinders



FEATURES

- Uses a revolutionary TEFC external motor design
- Drive motor is attached on the side and out from under the grind chamber, eliminating motor burnouts due to water damage
- Standard offset inlet on all units prevents accidental insertion of hands and other objects
- Auto reversing blades in all electric models
- 4" drain line
- 80 CFM required for air operation
- 5 gallons per minute water consumption
- Sink housing material is 304 stainless steel
- 10" standard rotor on all models
- Designed to withstand outdoor elements but silent enough to run indoors
- The electric 5 hp is explosion proof enclosure which exceeds Class I division II standards
- Meets and exceeds International Marpol 73/78 Annex V
- ABS approved



OPTIONS

- Magnetic Silverware Saver - magnetic catch guard at opening of disposal area – never lose silverware again
- Push rod is an OEM approved tool to eliminate foreign objects being put into unit
- Odour Enz environmentally safe enzyme odour eater for a cleaner tool
- Available in air, hydraulic, or electric driven



Push Rod Keeps Hands at a Safe Distance During Operation



Easy to Clean and Maintain



Overboard Discharge Outlet

TECHNICAL SPECIFICATION

UNIT	TUFF GUT
HOPPER CAPACITY	5 gal. / 19 litres
HEIGHT	36" / 914 mm
WIDTH	27" / 686 mm
DEPTH	27" / 686 mm
WEIGHT	396 lbs / 179 kg
HP	5, 7.5, 10, 15
REQUIREMENTS	Electric / Ex-proof, Air, Hyd.
LOAD CAPACITY	300 gallons/hr

MODEL	MEALS PER HOUR
5 HP ELECTRIC	2800 mph
7.5 HP ELECTRIC	3500 mph
10 HP ELECTRIC	4400 mph
15 HP ELECTRIC	5200 mph
AIR OPERATED	4100 mph
HYDRAULIC OPERATED	2800 mph

Note: All measurements are rounded up to the nearest whole unit or decimal.

First Choice in Compactors, Balers, Food Grinders, Crushers and Associated Services



sales@oegoffshore.com
www.oegoffshore.com